



Precision BEARING-SINGAPORE (PTE)LTD.



TIMKEN YCJ 15/16 SGT Flange Block Bearings

Bearing No. YCJ 15/16 SGT

YCJ 15/16 SGT Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	2.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.972
EAN	0087796265806
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	GY1015KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Square Flange Block; 15/16" Bore; 4" Bolt Circle; 2-49/64" Bolt Spacing; 1 Piece Solid; Set Screw Mount; Cast Iron; Ball Bearing; 1-11/32" Length Thru Bore; Relubricatable;



Precision BEARING-SINGAPORE (PTE)LTD.

Other Features	Single Row Normal Duty Wide Inner Race Corrosion Resistant Powder Coated Epoxy Finish
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	YCJ 15/16 SGT
Weight / LBS	2.136
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Nominal Bolt Circle Diameter Round	4 Inch 101.6 Millimeter
d	0.938 Inch 23.825 Millimeter
Bolt Spacing	2.766 Inch 70.256 Millimeter
D	1.344 Inch 34.13 Millimeter
Shaft Size d	15/16 in
Dimension D	2.563 in
Dimension E	1.575 in
Inside Ring Outside Diameter	1.334 in
Series	Industrial
Weight	2.07 lb
Seal Type	Shroud Seal
Total Length L	95.2 mm
Housing Width A	1.098 in
Bolt Hole Size N	10 mm
Flange Thickness A1	12.70 mm



Precision BEARING-SINGAPORE (PTE)LTD.

Center of Bearing from Housing End A2	19.4 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Total Height	95.2 mm
Bolt Size	M10
Center of Bearing from Bearing End S	14.3 mm
Static Load Rating	1750 lbf
Dynamic Load Rating	3490 lbf