



Precision BEARING-SINGAPORE (PTE)LTD.



4.331 Inch | 110 Millimeter x 7.874 Inch | 200 Millimeter x 2.087 Inch | 53 Millimeter TIMKEN NU2222EMA Cylindrical Roller Bearings

Bearing No. NU2222EMA

NU2222EMA Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	7.491
EAN	0053893773421
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	110MM Bore; Straight Bore Profile; 200MM Outside Diameter; 53MM Width;



Precision BEARING-SINGAPORE (PTE)LTD.

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
Category	Cylindrical Roller Bearings
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	NU2222EMA
Weight / LBS	16.5
B	2.087 Inch 53 Millimeter
D	7.874 Inch 200 Millimeter
d	4.331 Inch 110 Millimeter
Design Units	METRIC
Bearing Weight	7.5 Kg
Type	NU
Tapered Bore	N
d - Bore	110 mm
D - Outer Diameter	200 mm
C - Inner Ring Width	53 mm
B - Outer Ring Width	53 mm
C0 - Static Radial Rating	527000 N
C - Dynamic Radial Rating ¹	436000 N
Reference Thermal Speed Rating (Grease)	2400
Reference Thermal Speed Rating (Oil) ²	2800
Cg - Geometry Factor ³	0.1118
R - Inner Ring To Clear Radius ⁴	2.0 mm
r - Outer Ring To Clear Radius ⁵	2.0 mm



Precision BEARING-SINGAPORE (PTE)LTD.

da - Inner Ring Backing Diameter	127.000 mm
Da - Outer Ring Backing Diameter	0.000 mm